

# Contents

<b>Acknowledgments</b>	<b>v</b>
<b>Abstract</b>	<b>vii</b>
<b>List of figures</b>	<b>xviii</b>
<b>List of tables</b>	<b>xix</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Physics prospects for a future Linear Collider . . . . .	1
1.2 CLIC overview . . . . .	2
1.3 The CLIC Damping Rings . . . . .	4
1.4 Scope of the thesis . . . . .	6
<b>2 Beam dynamics and collective effects</b>	<b>7</b>
2.1 Linear beam optics . . . . .	7
2.1.1 Transverse betatron motion . . . . .	8
2.1.2 Longitudinal synchrotron motion . . . . .	13
2.2 Synchrotron radiation damping and quantum excitation . . . . .	14
2.3 Wake fields and impedances . . . . .	16
2.3.1 Longitudinal plane . . . . .	18
2.3.2 Transverse plane . . . . .	19
2.3.3 Effective impedance . . . . .	20
2.4 Electromagnetic simulation tools of wakefields and impedances . . . . .	21
2.4.1 CST Studio Suite . . . . .	21
2.4.2 ImpedanceWake2D . . . . .	21
<b>3 Transverse impedance budget of the CLIC DR</b>	<b>23</b>
3.1 Introduction . . . . .	23
3.2 The HEADTAIL code . . . . .	24
3.3 Transverse impedance budget . . . . .	25
3.3.1 Impedance model with a broad-band resonator . . . . .	25
3.3.2 Impedance model with a broad-band resonator and resistive wall . . . . .	31
3.4 Effect of coating thickness and properties at high frequencies . . . . .	37
3.5 Injection and extraction kickers . . . . .	40

<b>4</b>	<b>Electromagnetic properties of NEG at high frequencies</b>	<b>43</b>
4.1	Motivation . . . . .	43
4.2	Waveguide method and CST simulation . . . . .	43
4.2.1	Method . . . . .	43
4.2.2	Benchmark with known materials . . . . .	45
4.2.3	S parameters . . . . .	46
4.2.4	Network analyzer . . . . .	47
4.3	Measurements with a stainless steel waveguide in X-band . . . . .	47
4.4	Measurements with a copper waveguide in X-band . . . . .	51
4.5	Measurements of NEG on a copper waveguide in X-band . . . . .	54
4.5.1	NEG coating process . . . . .	54
4.5.2	NEG-coated Cu waveguide measurement results . . . . .	54
4.5.3	Error analysis for CST simulations . . . . .	57
4.5.4	Conclusions about the NEG conductivity in X-band . . . . .	63
4.6	NEG properties characterization above 200 GHz . . . . .	64
4.6.1	220-330 GHz: WR-3.4 waveguides . . . . .	64
4.6.2	500-750 GHz: WR-1.5 waveguides . . . . .	70
4.7	Effect of the non-uniform coating profile . . . . .	73
4.8	Effect on the transverse impedance budget of the DRs . . . . .	80
<b>5</b>	<b>Studies on existing and future light sources</b>	<b>83</b>
5.1	Single bunch measurements in the ALBA storage ring . . . . .	83
5.1.1	TMCI measurements at 0 chromaticity and HEADTAIL simulations . . . . .	84
5.1.2	Study of the injection kickers . . . . .	90
5.1.3	TMCI measurements at 0 chromaticity to study the effect of the pinger magnet . . . . .	98
5.2	Impedance studies for the SLS2 upgrade . . . . .	101
5.2.1	Motivation . . . . .	101
5.2.2	Transverse resistive wall impedance and instability thresholds at zero chromaticity . . . . .	102
5.2.3	Transverse resistive wall impedance and instability thresholds at positive and negative chromaticity . . . . .	103
5.2.4	Comparative study with higher negative momentum compaction factor lattice (ca05q) . . . . .	109
5.2.5	Transverse resistive wall impedance and instability thresholds at zero chromaticity for the ca05q lattice . . . . .	109
	<b>Conclusions</b>	<b>113</b>
<b>A</b>	<b>HEADTAIL simulations parameters for the CLIC DR</b>	<b>115</b>
A.1	Broad-band resonator model with 0 chromaticity . . . . .	115
A.2	Broad-band resonator model with positive chromaticity . . . . .	117

<b>B ImpedanceWake2D parameters</b>	<b>119</b>
B.1 Wigglers: 2 $\mu\text{m}$ NEG coating on StSt chamber . . . . .	119
B.2 Arcs: 2 $\mu\text{m}$ NEG coating on StSt chamber . . . . .	120
B.3 Rest: 2 $\mu\text{m}$ NEG coating on StSt chamber . . . . .	120
B.4 Wigglers: 1 $\mu\text{m}$ or 2 $\mu\text{m}$ NEG coating on StSt chamber . . . . .	121
B.5 Wigglers: 0.5 $\mu\text{m}$ or 1 $\mu\text{m}$ aC coating on StSt chamber . . . . .	122
<b>C CST and ImpedanceWake2D comparison</b>	<b>123</b>
C.1 Compare coating feature for a lossy substrate . . . . .	123
<b>D Simulations parameters for SLS2</b>	<b>124</b>
D.1 Resistive wall impedance calculation of SLS2 with ImpedanceWake2D . . . . .	124
<b>Curriculum Vitae</b>	<b>131</b>