

# Contents

<b>List of Figures</b>	<b>ix</b>
<b>Introduction</b>	<b>1</b>
<b>1 Brillouin scattering</b>	<b>5</b>
1.1 Spontaneous Brillouin scattering . . . . .	6
1.2 Stimulated Brillouin scattering . . . . .	8
1.2.1 Acoustic wave . . . . .	10
1.2.2 Optical waves . . . . .	12
1.2.3 Small gain approximation . . . . .	13
1.3 Temperature/strain dependence of the SBS . . . . .	15
<b>2 Phase-correlated sensing</b>	<b>17</b>
2.1 Localising the Brillouin interaction by phase modulation . . . . .	17
2.1.1 Scanning the position of the correlation peak . . . . .	20
2.2 Spatial resolution . . . . .	21
2.2.1 Correlation peak shape . . . . .	21
2.2.2 Correlation peak response . . . . .	24
2.2.3 Spatial resolution and sampling interval . . . . .	25
2.3 Experiment . . . . .	28
2.3.1 Setup . . . . .	28
2.3.2 Measurement . . . . .	29
2.3.3 Spatial resolution . . . . .	30
2.3.4 Spectral filtering of phase-modulated signal . . . . .	31
2.4 Discussion . . . . .	32
<b>3 Time-gated phase-correlation technique</b>	<b>35</b>
3.1 Time gating . . . . .	35
3.1.1 Experimental setup . . . . .	36
3.1.2 Time-domain traces . . . . .	38

---

3.2	Optimal pump pulse duration . . . . .	40
3.2.1	Pump pulse duration and the system's response . . . . .	40
3.2.2	Experimental verification . . . . .	42
3.3	Experiment . . . . .	44
3.3.1	Measurement along a 17.5 km long fibre . . . . .	44
3.3.2	Spatial resolution . . . . .	45
3.3.3	Brillouin scattering in tapered fibres . . . . .	47
3.4	Discussion . . . . .	50
<b>4</b>	<b>Addressing the limits</b> . . . . .	<b>53</b>
4.1	Power limitations . . . . .	53
4.2	Number of points and measurement time . . . . .	54
4.2.1	Spatial resolution improvement . . . . .	55
4.2.2	Distance improvement . . . . .	56
4.2.3	Finding an optimal bit duration . . . . .	57
4.3	Temperature-dependent position of correlation peaks . . . . .	58
4.3.1	Uniform temperature shift . . . . .	59
4.3.2	Arbitrary temperature distribution . . . . .	59
4.4	Discussion . . . . .	64
<b>5</b>	<b>Brillouin dynamic gratings in polarisation-maintaining fibres</b> . . . . .	<b>65</b>
5.1	Brillouin dynamic gratings theory . . . . .	65
5.1.1	BDG generation . . . . .	66
5.1.2	Reflection from a dynamic grating . . . . .	68
5.2	Flip-flop . . . . .	71
5.2.1	Experimental setup . . . . .	72
5.2.2	Reflection of two pulses . . . . .	74
5.3	Spectral properties of dynamic Brillouin gratings . . . . .	82
5.3.1	Reflection spectrum of a BDG . . . . .	82
5.3.2	Dynamic grating with multiple spectral lines . . . . .	83
5.3.3	Dynamic gratings in multiple fibres . . . . .	86
5.4	Discussion . . . . .	88
	<b>Conclusions and perspectives</b> . . . . .	<b>89</b>
<b>A</b>	<b>Correlation peak shape derivation</b> . . . . .	<b>93</b>
<b>B</b>	<b>Solving the differential equation for dynamic grating reflection</b> . . . . .	<b>97</b>
	<b>Bibliography</b> . . . . .	<b>101</b>