

# Contents

<b>Acknowledgements</b>	<b>i</b>
<b>Abstract (English/Deutsch)</b>	<b>iii</b>
<b>1 Introduction</b>	<b>1</b>
1.1 mmWave Wireless Communication . . . . .	4
1.2 mmWave Usage Scenarios . . . . .	5
1.3 Overview mmWave Research Challenges . . . . .	7
1.4 Contributions . . . . .	9
1.5 Outline of the Thesis . . . . .	10
1.6 Third-Party Contributions . . . . .	11
1.7 Notation . . . . .	12
<b>2 mmWave Wireless LAN Receiver</b>	<b>13</b>
2.1 mmWave Environment & Standards . . . . .	14
2.1.1 Free Space Path Loss and Array Gain . . . . .	14
2.1.2 60 GHz Indoor Channel Models . . . . .	16
2.1.3 60 GHz Wireless Communication Standards . . . . .	18
2.1.4 IEEE 802.11ad Single-Carrier Frame Format . . . . .	19
2.2 Algorithms and Implementations . . . . .	22
2.2.1 Time-Domain vs. Frequency-Domain Architectures . . . . .	22
2.2.2 Synchronization . . . . .	24
2.3 Single-Carrier Frequency-Domain Equalization . . . . .	37
2.3.1 Cyclic-Prefix SC-FDE . . . . .	37
2.3.2 Extension of SC-FDE . . . . .	40
2.3.3 SC-FDE Baseband Architecture . . . . .	43
2.3.4 Energy Proportional Frequency-Domain Equalization . . . . .	44
2.4 Soft-Output Delayed Decision Feedback Sequence Estimation . . . . .	51
2.4.1 System Model . . . . .	52
2.4.2 Algorithm . . . . .	52
2.4.3 Baseline Architecture . . . . .	58
2.4.4 Optimized Architecture . . . . .	58
2.4.5 Results . . . . .	65
2.5 11ad Baseband Implementation in 40nm CMOS . . . . .	67
	<b>vii</b>

2.5.1	Architecture . . . . .	69
2.5.2	Implementation . . . . .	70
2.6	Summary . . . . .	72
<b>3</b>	<b>Complex Sub-Sampling Receiver</b>	<b>75</b>
3.1	Sub-Sampling Receiver . . . . .	77
3.2	Complex Sub-Sampling . . . . .	81
3.2.1	Non-Ideal Complex Sub-Sampling . . . . .	83
3.2.2	Non-Ideal Coupler Compensation . . . . .	85
3.3	DSP for Complex Sub-Sampling . . . . .	88
3.4	Noise Characterization in Sub-Sampling Receiver . . . . .	91
3.5	Single Oscillator Receiver . . . . .	92
3.6	Summary . . . . .	94
<b>4</b>	<b>Testbed for High-Rate mmWave Communication</b>	<b>95</b>
4.1	Architecture . . . . .	96
4.1.1	60 GHz RF Frontends . . . . .	96
4.1.2	Link Budget Analysis . . . . .	100
4.2	Testbed Characterization . . . . .	103
4.2.1	Coupler Compensation Calibration . . . . .	103
4.2.2	Compression . . . . .	111
4.2.3	Common Frequency Selectivity . . . . .	114
4.3	Measurement Considerations . . . . .	114
4.4	Summary . . . . .	116
<b>5</b>	<b>Information-Driven Modulation and Coding</b>	<b>119</b>
5.1	Information-Driven Modulation . . . . .	119
5.2	Amplitude Phase Shift Keying (APSK) . . . . .	121
5.2.1	Meric APSK constellations . . . . .	123
5.2.2	Asymmetrical Meric APSK . . . . .	125
5.2.3	Symbol Mapping & Demapping . . . . .	127
5.3	Polar Coding for APSK . . . . .	135
5.3.1	Optimal Code-Rate . . . . .	136
5.3.2	Introduction to Polar Codes . . . . .	136
5.3.3	High-Modulation Order Trained Polar Codes . . . . .	138
5.3.4	Multi-Rate Polar Code Evaluation . . . . .	140
5.4	APSK-Polar Codes Testbed Measurements . . . . .	142
5.4.1	Average Mutual Information on the Testbed . . . . .	143
5.4.2	Error Rate Measurements on the Testbed . . . . .	144
5.5	Summary . . . . .	145
<b>6</b>	<b>Summary and Conclusions</b>	<b>149</b>

<b>A Appendix</b>	<b>153</b>
A.1 Gaussian Channel Capacity . . . . .	153
A.2 SNR and EVM Definition . . . . .	154
A.3 Log-Likelihood Ratio (LLR) . . . . .	154
A.4 Max-Log Log-Likelihood Ratio (max-log LLR) . . . . .	156
A.5 Average Mutual Information (AMI) . . . . .	156
<b>Acronyms</b>	<b>157</b>
<b>Bibliography</b>	<b>177</b>
<b>List of Figures</b>	<b>178</b>
<b>List of Tables</b>	<b>185</b>
<b>Curriculum Vitae</b>	<b>187</b>